

EKSPĻUATĀCIJAS ĪPAŠĪBU DEKLARĀCIJA **N. CPR-IT1/0488**

- 1) Unikāls produkta tipa identifikācijas kods: **PLASTIMUL 1K SUPER PLUS**
- 2) Paredzētais pielietojums: **Ar polimēriem modificēts bitumena bāzes biezs pārklājums (PMBC – W2A, CB2, C2A) hidroizolācijas izveidei zem zemes esošām konstrukcijām**
- 3) Ražotājs: MAPEI S.p.A. – **Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Sistēma AVCP: Sistēma 3
- 5) Vienotais standarts: EN 15814: 2011 + A2: 2014

Izpildinstitūcijas: **Laboratorija Materialprüfungsamt Nordrhein-Westfalen (MPA NRW), N. 0432 veikusi veikspējas (ūdens necaurlaidība) novērtējumu, pamatojoties uz testa paraugiem, ko iesniedzis ražotājs.**

Laboratorija CSI S.p.A., N. 0672 veikusi novērtējumu (ugunsdrošības noteikšana), pamatojoties uz testa paraugiem, ko iesniedzis ražotājs.

- 6) Deklarētās veikspējas īpašības:

Būtiskākie raksturlielumi	Ekspluatācijas īpašības
Ūdens necaurlaidība Plaisu pārsegtspēja: Ūdens noturība Elastība zemā temperatūrā Izmēru stabilitāte augstās temperatūrās Uguns reakcija Noturība pret spiedi Bīstamas sastāvdaļas Ūdens necaurlaidības un ugunsizturības ilgtspējība	Klase W2A Klase CB2 Atbilst Atbilst Atbilst Klase E Klase C2A NPD Atbilst

Augstāk norādītā produkta veikspēja atbilst deklarētajām īpašībām.

Šī ekspluatācijas īpašību deklarācija ir izsniegta saskaņā ar Regulu (ES) Nr 305/2011, ar pilnu iepriekš norādītā ražotāja atbildību.

Parakstīts ražotāja vārdā: Paolo Murelli – Korporatīvā Kvalitātes Vadība

Milāna, 08/02/2016

EĪD PDF formātā ir pieejamas Mapei mājas lapā

Pārskats 1 piezīmes:	Nemainīgs produkts, standarta atsauces datums atjaunināts
-----------------------------	--

 0432, 0672	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
14 CPR-IT1/0488 EN 15814 PLASTIMUL 1K SUPER PLUS <i>Polymer modified bituminous thick coating (PMBC–W2A, CB2, C2A) for waterproofing in below ground structures</i>	
Watertightness	Class W2A
Crack bridging ability	Class CB2
Water resistance	Pass
Flexibility at low temperature	Pass
Dimensional stability at high temperatures	Pass
Reaction to fire	Class E
Resistance to compression	Class C2A
Dangerous substances	NPD
Durability of water tightness and reaction to fire	Pass

Piezīme:

MAPEI nodrošina šo pielikumu kopā ar EĪD, lai atvieglotu CE marķējuma skaidrojumu starptautiskajiem klientiem. Pievienotais CE marķējums var būt nedaudz atšķirīgs, salīdzinot ar to, kas norādīts uz attiecīgā iepakojuma vai dokumentācijas, jo:

- Dēļ grafiskā pielāgojuma uz iepakojuma vai izmantotās drukāšanas metodes,
- Dēļ valodu atšķirības (viens iepakojums vairākām valstīm),
- produkts ir jau krājumā uz brīdi, kad tiek ieviests CE marķējuma atjauninājums,
- Drukas kļūdas dēļ.

DECLARATION OF PERFORMANCE N. CPR-IT1/0488

- 1) Unique identification code of the product-type: **PLASTIMUL 1K SUPER PLUS**
- 2) Intended uses: **Polymer modified bituminous thick coating (PMBC-W2A, CB2, C2A) for waterproofing in below ground structures**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 3**
- 5) Harmonized standards: **EN 15814 :2011+A2:2014**

Notified bodies: **the notified laboratory Materialprüfungsamt Nordrhein-Westfalen (MPA NRW), N. 0432, carried out the assessment of the performance (watertightness) on the basis of testing on samples taken by the manufacturer.**

The notified laboratory Universität Stuttgart für die Materialprüfungsanstalt Universität Stuttgart (MPA Stuttgart, Otto-Graf-Institut, FMFA), N. 0672, carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer.

- 6) Performances declared:


Essential characteristics	Performances
Watertightness	Class W2A
Crack bridging ability	Class CB2
Water resistance	Pass
Flexibility at low temperature	Pass
Dimensional stability at high temperatures	Pass
Reaction to fire	Class E
Resistance to compression	Class C2A
Dangerous substances	NPD
Durability of water tightness and reaction to fire	Pass

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**

Milan, 08/02/2016



DoP in Pdf format are available in the Mapei website.

Revision 1 notes:	Unchanged product, standard reference date updated
--------------------------	---

PLASTIMUL 1K SUPER PLUS
CE MARKING
Annex to DoP N. CPR-IT1/0488



 0432, 0672	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
14 CPR-IT1/0488 EN 15814 PLASTIMUL 1K SUPER PLUS <i>Polymer modified bituminous thick coating (PMBC–W2A, CB2, C2A) for waterproofing in below ground structures</i>	
Watertightness	Class W2A
Crack bridging ability	Class CB2
Water resistance	Pass
Flexibility at low temperature	Pass
Dimensional stability at high temperatures	Pass
Reaction to fire	Class E
Resistance to compression	Class C2A
Dangerous substances	NPD
Durability of water tightness and reaction to fire	Pass

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.