

**Ekspluatācijas īpašību deklarācija Nr. CPR-IT4 / B0305
REV.08/11/2021**

- 1) Unikāls produkta tipa identifikācijas kods: **ELASTOFLEX HP P**
- 2) Paredzētais pielietojums: **Pastiprināta bitumena membrāna betona tiltu klāju un citu betona zonu hidroizolācijai**
- 3) Ražotājs: **POLYGLASS S.P.A Via Giorgio Squinzi 2 -31047 Ponte di Piave (TV) ITALIA - www.polyglass.com**
- 4) Sistēma VVCP: **Sistēma 2+**
- 5) Vienotais standarts: **EN 14695:2010+AC:2011**

Izpildinstitūcijas: **BUREAU VERITAS ITALIA S.P.A. , N. 1370**

- 6) Deklarētās veiktspējas īpašības:

Būtiskākie raksturlielumi	Ekspluatācijas īpašības
Ūdens necaurlaidība	Atbilst
Stiepes īpašības:	Stiepes izturība (L/T): 1200/1000 (±20%) N/50 mm Pagarinājums (L/T): 50/50 (±15) %
Adhēzijas stiprība	≥ 0.8 N/mm²
Plaisu pārklājspēja	≤ -20 °C
Savienojamība ar citiem produktiem	≥ 200 %
Elastība zemā temperatūrā	≤ -25 °C
Bīdes noturība	≥ 0,25 N/mm²
Reakcija pret mastikas asfalta uzklāšanu:	(S) NPD (Δt) NPD (i) NPD
Izturība pret asfalta slāņa sablīvēšanos	Atbilst
Ilgmūžība:	Ūdens absorbētspēja: NPD Saderība: NPD Termiskās novecošanās izpausmes: Elastība zemā temperatūrā ≤ -15 °C Plūsmas pretestība paaugstinātā temperatūrā: ≥ 100 °C
Bīstamas vielas	NPD

Augstāk norādītā produkta veiktspēja atbilst deklarētajām īpašībām.

Šī ekspluatācijas īpašību deklarācija ir izsniegta saskaņā ar Regulu (ES) Nr 305/2011, ar pilnu iepriekš norādītā ražotāja atbildību.

Parakstīts ražotāja vārdā: **Ing. P. Ciferri** In **Ponte di Piave**,
08/11/2021

REACH informācija: šis ir izstrādājums saskaņā ar REACH Regulas (EK) Nr. 1907/2006 un saskaņā ar iepriekš minētās regulas 31. un 33. pantu neprasa nekādu drošības datu lapu. Lietojot izstrādājumu, pievērst uzmanību tehnisko datu lapā dotajiem ieteikumiem un darba vietā noteiktajām drošības prasībām

DoP ir pieejams Pdf formātā Polyglass SpA vietnē.

 1370	 POLYGLASS S.P.A Via Giorgio Squinzi 2 -31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
14. CPR-IT4/ B0305 rev. 08/11/2021 EN 14695:2010 ELASTOFLEX HP P <i>Reinforced bitumen sheet for waterproofing of concrete bridge decks and other trafficked areas of concrete</i>	
Watertightness	Pass
Tensile properties:	Tensile strength (L/T): 1200/1000 ($\pm 20\%$) N/50 mm Elongation (L/T): 50/50 ($\pm 15\%$) %
Bond strength	≥ 0.8 N/mm ²
Capacity to bridge cracks	≤ -20 °C
Compatibility	≥ 200 %
Flexibility at low temperature	≤ -25 °C
Resistance to shear	$\geq 0,25$ N/mm ²
Resistance to compaction of an asphalt layer	Pass
Durability:	Thermal ageing behaviour: Flexibility at low temperature: ≤ -15 °C Flow resistance at elevated temperature: ≥ 100 °C
Dangerous substances	NPD

Piezīme:

MAPEI nodrošina šo pielikumu kopā ar EĪD, lai atvieglotu CE marķējuma skaidrojumu starptautiskajiem klientiem. Pievienotais CE marķējums var būt nedaudz atšķirīgs, salīdzinot ar to, kas norādīts uz attiecīgā iepakojuma vai dokumentācijas, jo:

- NPD (Veiktspēja nav noteikta) vērtības var tikt mainītas CE marķējumā
- Dēļ grafiskā pielāgojuma uz iepakojuma vai izmantotās drukāšanas metodes,
- Dēļ valodu atšķirības (viens iepakojums vairākām valstīm),
- produkts ir jau krājumā uz brīdi, kad tiek ieviests CE marķējuma atjauninājums,
- Drukas kļūdas dēļ.

Declaration of performance N. CPR-IT4/ B0305 rev. 08/11/2021

- 1) Unique identification code of the product-type: ELASTOFLEX HP P
- 2) Intended uses: Reinforced bitumen sheet for waterproofing of concrete bridge decks and other trafficked areas of concrete
- 3) Manufacturer: POLYGLASS S.P.A Via Giorgio Squinzi 2 -31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
- 4) System of VVCP: System 2+
- 5) Harmonized standards: 14695:2010+AC:2011

Notified bodies: BUREAU VERITAS ITALIA S.P.A. , N. 1370

6) Performances declared:

Essential characteristics	Performances
Watertightness	Pass
Tensile properties:	Tensile strength (L/T): 1200/1000 ($\pm 20\%$) N/50 mm Elongation (L/T): 50/50 ($\pm 15\%$) %
Bond strength	≥ 0.8 N/mm ²
Capacity to bridge cracks	≤ -20 °C
Compatibility	≥ 200 %
Flexibility at low temperature	≤ -25 °C
Resistance to shear	$\geq 0,25$ N/mm ²
Behaviour during application of mastic asphalt:	(S) NPD (Δt) NPD (i) NPD
Resistance to compaction of an asphalt layer	Pass
Durability:	Water adsorption: NPD Compatibility: NPD Thermal ageing behaviour: Flexibility at low temperature ≤ -15 °C Flow resistance at elevated temperature: ≥ 100 °C
Dangerous substances	NPD

The performance of the product identified above is in conformity with the set of declared performances.
This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Ing. P. Ciferri
In Ponte di Piave, 08/11/2021

..... 

REACH information: this is an article in accordance with Article 3 of the REACH Regulation (EC) No 1907/2006 and pursuant to Article 31 and 33 of the above-mentioned Regulation does not require any Safety Data Sheet. While using the product, pay attention to the recommendations written in the Technical Data Sheet and to the safety requirements laid down in the workplace.

DoP are available in Pdf format on Polyglass SpA website.

Version: 4

Unchanged product. The manufacturer contact address has been updated.

 1370	 POLYGLASS S.P.A Via Giorgio Squinzi 2 -31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
14 CPR-IT4/ B0305 rev. 08/11/2021 EN 14695:2010 ELASTOFLEX HP P <i>Reinforced bitumen sheet for waterproofing of concrete bridge decks and other trafficked areas of concrete</i>	
Watertightness	Pass
Tensile properties:	Tensile strength (L/T): 1200/1000 ($\pm 20\%$) N/50 mm Elongation (L/T): 50/50 ($\pm 15\%$) %
Bond strength	≥ 0.8 N/mm ²
Capacity to bridge cracks	≤ -20 °C
Compatibility	≥ 200 %
Flexibility at low temperature	≤ -25 °C
Resistance to shear	$\geq 0,25$ N/mm ²
Resistance to compaction of an asphalt layer	Pass
Durability:	Thermal ageing behaviour: Flexibility at low temperature: ≤ -15 °C Flow resistance at elevated temperature: ≥ 100 °C
Dangerous substances	NPD

Nota:

POLYGLASS supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the CE marking,
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.