

Ekspluatācijas īpašību deklarācija Nr. CPR-IT4 / B0362
REV.09/07/2019

- 1) Unikāls produkta tipa identifikācijas kods: ELASTOFLEX SA P
- 2) Paredzētais pielietojums: Hidroizolācijas apakšklājs nepārtrauktam jumta segumam
- 3) Ražotājs: [POLYGLASS S.P.A Via Dell'Artigianato, 34-31047 Ponte di Piave \(TV\) ITALIA - www.polyglass.com](http://www.polyglass.com)
- 4) Sistēma VVCP: **Sistēma 3**
- 5) Vienotais standarts: **EN 13859-1:2010**

Izpildinstitūcija:

Laboratorija ITC, N. 0970, veikusi veikspējas novērtējumu (uguns reakcija), pamatojoties uz testa paraugiem, ko iesniedzis ražotājs.

Laboratorija EMI, N.1417, veikusi veikspējas novērtējumu (uguns reakcija), pamatojoties uz testa paraugiem, ko iesniedzis ražotājs.

- 6) Deklarētās veikspējas īpašības:

Būtiskākie raksturlielumi	Ekspluatācijas īpašības
Uguns reakcija	Klase E
Izturība pret sakņu cauraugšanu	Klase W1
Stiepes īpašības Stiepes izturība (gareniski / šķērsvirzienā) Pagarinājums (gareniski / šķērsvirzienā)	400/300 ($\pm 20\%$) N/50 mm 35/35 ($\pm 15\%$) %
Izturība pret plīsumiem (gareniski / šķērsvirzienā)	150/150 ($\pm 30\%$) N
Elastība zemas temperatūras apstākļos	$\leq -20\text{ }^{\circ}\text{C}$
Mākslīgās novecināšanas izpausmes: Ūdens necaurlaidība: Stiepes izturība (gareniski / šķērsvirzienā) Pagarinājums (gareniski / šķērsvirzienā)	W1 $\pm 30\%$ V.I. -30% V.I.
Bīstamas sastāvdaļas	NPD

Saskaņā ar REACH regulu (EK) Nr. 1907/2006, šis ir izstrādājums, un saskaņā ar šīs regulas 31. un 33. punktu, produktam drošības datu lapas nav nepieciešamas. Lietojot izstrādājumu, pievērst uzmanību tehnisko datu lapā dotajiem ieteikumiem un darba vietā noteiktajām drošības prasībām

Augstāk norādītā produkta veikspēja atbilst deklarētajām īpašībām.

Šī ekspluatācijas īpašību deklarācija ir izsniegta saskaņā ar Regulu (ES) Nr 305/2011, ar pilnu iepriekš norādītā ražotāja atbildību.

Parakstīts ražotāja vārdā: [Ing. P. Ciferri](#)

In Ponte di Piave 09/07/2019

.....

EID PDF formātā ir pieejamas Polyglass SpA mājas lapā.

2. versija:

Nemainīgs produkts, atjaunota EID forma

 0970 1417	 Via Dell'Artigianato, 34 31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
14 CPR-IT4/ B0362 rev. 09/07/2019 EN 13859-1 ELASTOFLEX SA P Waterproofing underlayer for discontinuous roofing	
Reaction to fire	Classe E
Resistance to water penetration	Classe W1
Tensile properties Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	400/300 (±20%) N/50 mm 35/35 (±15) %
Resistance to tearing (longitudinal/transverse)	150/150 (±30%) N
Flexibility at low temperature	≤ -20 °C
Artificial ageing behaviour concerning: Resistance to water penetration Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	W1 ± 30% V.I. -30% V.I.
Dangerous substances	NPD

Piezīme:

MAPEI nodrošina řo pielikumu kopā ar EĢD, lai atvieglotu CE marķējuma skaidrojumu starptautiskajiem klientiem. Pievienotais CE marķējums var būt nedaudz atšķirīgs, salīdzinot ar to, kas norādīts uz attiecīgā iepakojuma vai dokumentācijas, jo:

- Dēļ grafiskā pielāgojuma uz iepakojuma vai izmantotās drukāšanas metodes,
- Dēļ valodu atšķirības (viens iepakojums vairākām valstīm),
- produkts ir jau krājumā uz brīdi, kad tiek ieviests CE marķējuma atjauninājums,
- Drukas kļūdas dēļ.

Declaration of performance N. CPR-IT4/ B0362 rev. 09/07/2019

- 1) Unique identification code of the product-type: **ELASTOFLEX SA P**
- 2) Intended uses: **Waterproofing underlayer for discontinuous roofing**
- 3) Manufacturer: **POLYGLASS S.P.A Via Dell'Artigianato, 34-31047 Ponte di Piave (TV) ITALIA - www.polyglass.com**
- 4) System of VVCP: **System 3**
- 5) Harmonized standards: **EN 13859-1:2010**

Notified bodies:

The notified laboratory ITC, N. 0970, carried out the assessment of the performance (resistance to water penetration) on the basis of testing on samples taken by the manufacturer.

The notified laboratory EMI, N.1417, carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer.

6) Performances declared:

Essential characteristics	Performances
Reaction to fire	Classe E
Resistance to water penetration	Classe W1
Tensile properties Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	400/300 (±20%) N/50 mm 35/35 (±15) %
Resistance to tearing (longitudinal/transverse)	150/150 (±30%) N
Flexibility at low temperature	≤ -20 °C
Artificial ageing behaviour concerning: Resistance to water penetration Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	W1 ±30% V.I. -30% V.I.
Dangerous substances	NPD

This is an article in accordance with Article 3 of the REACH regulation (EC) no. 1907/2006 and pursuant to Article 31 and 33 of the a/m regulation does not require any Safety Data Sheet. While using the product, pay attention to the recommendations written in the Technical Data Sheet and to the safety requirements laid down in the workplace

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Ing. P. Ciferri**



In Ponte di Piave 09/07/2019

.....

DoP in Pdf format are available in the Polyglass SpA website.

Version 2	Unchanged product, DoP layout updated
-----------	---------------------------------------

 0970 1417	 Via Dell'Artigianato, 34 31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
14 CPR-IT4/ B0362 rev. 09/07/2019 EN 13859-1 ELASTOFLEX SA P Waterproofing underlayer for discontinuous roofing	
Reaction to fire	Classe E
Resistance to water penetration	Classe W1
Tensile properties Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	400/300 (±20%) N/50 mm 35/35 (±15) %
Resistance to tearing (longitudinal/transverse)	150/150 (±30%) N
Flexibility at low temperature	≤ -20 °C
Artificial ageing behaviour concerning: Resistance to water penetration Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	W1 ±30% V.I. -30% V.I.
Dangerous substances	NPD

Note:

Polyglass supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*