

**Ekspluatācijas īpašību deklarācija Nr. CPR-IT4 / B1274
REV.16/04/2020**

- 1) Unikāls produkta tipa identifikācijas kods: POLYVAP SA P-AL
- 2) Paredzētais pielietojums: Bitumena ūdens tvaiku kontroles slāņi
- 3) Ražotājs: [POLYGLASS S.P.A Via Dell'Artigianato, 34-31047 Ponte di Piave \(TV\) ITALIA - www.polyglass.com](http://www.polyglass.com)
- 4) Sistēma VVCP: [Sistēma 3](#)
- 5) Vienotais standarts: EN 13970:2004 + A1:2006

Izpildinstitūcijas:

Laboratorija CSI S.p.A., N. 0497, veikusi veikspējas novērtējumu (ūdens necaurlaidība un ūdens tvaiku caurlaidība), pamatojoties uz testa paraugiem, ko iesniedzis ražotājs.

Laboratorija EMI, N.1417, veikusi veikspējas novērtējumu (uguns reakcija), pamatojoties uz testa paraugiem, ko iesniedzis ražotājs.

- 6) Deklarētās veikspējas īpašības:

Būtiskākie raksturlielumi	Ekspluatācijas īpašības
Uguns reakcija	Klase E
Ūdensnecaurlaidība (B metode)	Atbilst prasībām
Stiepes īpašības Stiepes izturība (gareniski / šķērsvirzienā) Pagarinājums (gareniski / šķērsvirzienā)	400/200 ($\pm 20\%$) N/50 mm 30/30 ($\pm 15\%$) %
Izturība pret statisko slodzi (A metode)	≥ 600 mm
Izturība pret plūsumiem (gareniski / šķērsvirzienā)	100/100 ($\pm 30\%$) N
Savienojuma vietu stiprība Bīdes pretestība	NPD
Elastība zemā temperatūrā	≤ -25 °C
Ūdens tvaiku caurlaidība	$\geq 1.000.000$ μ
Ilgmūžība Pēc mākslīgas novecošanas Pret ķīmiskām vielām	$\pm 50\%$ V.I. $\pm 50\%$ V.I.
Bīstamas sastāvdaļas	NPD

Saskaņā ar REACH regulu (EK) Nr. 1907/2006, šis ir izstrādājums, un saskaņā ar šīs regulas 31. un 33. punktu, produktam drošības datu lapas nav nepieciešamas. Lietojot izstrādājumu, pievērst uzmanību tehnisko datu lapā dotajiem ieteikumiem un darba vietā noteiktajām drošības prasībām

Augstāk norādītā produkta veikspēja atbilst deklarētajām īpašībām.

Šī ekspluatācijas īpašību deklarācija ir izsniegta saskaņā ar Regulu (ES) Nr 305/2011, ar pilnu iepriekš norādītā ražotāja atbildību.

Parakstīts ražotāja vārdā: [Ing. P. Ciferri](#)

In Ponte di Piave 16/04/2020

.....

EID PDF formātā ir pieejamas Polyglass SpA mājas lapā.

Pārskats 1 piezīme:	Nemainīgs produkts, atjaunota EID forma
---------------------	---



POLYVAP SA P-AL
CE
Pielikums Ekspluatācijas īpašību
deklarācijai Nr. CPR-IT4
/ B1274
REV.16/04/2020

 0497 1417	 Via Dell'Artigianato, 34 31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
14 CPR-IT4/ B1274 rev. 16/04/2020 EN 13970 POLYVAP SA P-AL Bitumen water vapour control layers	
Reaction to fire	Classe E
Watertightness (Method B)	Meet requirements
Tensile properties Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	400/200 ($\pm 20\%$) N/50 mm 30/30 ($\pm 15\%$) %
Resistance to static loading (Method A)	≥ 600 mm
Resistance to tearing (longitudinal/transverse)	100/100 ($\pm 30\%$) N
Flexibility at low temperature	≤ -25 °C
Water vapor permeability	$\geq 1.000.000$ μ
Durability After exposure to artificial ageing Against chemicals	$\pm 50\%$ V.I. $\pm 50\%$ V.I.
Dangerous substances	NPD

Note:

MAPEI nodrošina šo pielikumu kopā ar EĪD, lai atvieglotu CE marķējuma skaidrojumu starptautiskajiem klientiem. Pievienotais CE marķējums var būt nedaudz atšķirīgs, salīdzinot ar to, kas norādīts uz attiecīgā iepakojuma vai dokumentācijas, jo:

- Dēļ grafiskā pielāgojuma uz iepakojuma vai izmantotās drukāšanas metodes,
- Dēļ valodu atšķirības (viens iepakojums vairākām valstīm),
- produkts ir jau krājumā uz brīdi, kad tiek ieviests CE marķējuma atjauninājums,
- Drukas kļūdas dēļ.

Declaration of performance N. CPR-IT4/ B1274 rev. 16/04/2020

- 1) Unique identification code of the product-type: POLYVAP SA P-AL
- 2) Intended uses: Bitumen water vapour control layers
- 3) Manufacturer: POLYGLASS S.P.A Via Dell'Artigianato, 34-31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
- 4) System of VVCP: System 3
- 5) Harmonized standards: EN 13970:2004 + A1:2006

Notified bodies:

The notified laboratory CSI, N. 0497, carried out the assessment of the performance (Watertightness and Water vapor permeability) on the basis of testing on samples taken by the manufacturer.

The notified laboratory EMI, N.1417 carried out the assessment of the performance (Reaction to fire) on the basis of testing on samples taken by the manufacturer.

6) Performances declared:

Essential characteristics	Performances
Reaction to fire	Classe E
Watertightness (Method B)	Meet requirements
Tensile properties Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	400/200 ($\pm 20\%$) N/50 mm 30/30 ($\pm 15\%$) %
Resistance to impact (Method A)	≥ 600 mm
Resistance to tearing (longitudinal/transverse)	100/100 ($\pm 30\%$) N
Joint strength Shear resistance	NPD
Flexibility at low temperature	≤ -25 °C
Water vapor permeability	$\geq 1.000.000$ μ
Durability After exposure to artificial ageing Against chemicals	$\pm 50\%$ V.I. $\pm 50\%$ V.I.
Dangerous substances	NPD

This is an article in accordance with Article 3 of the REACH regulation (EC) no. 1907/2006 and pursuant to Article 31 and 33 of the a/m regulation does not require any Safety Data Sheet. While using the product, pay attention to the recommendations written in the Technical Data Sheet and to the safety requirements laid down in the workplace

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Ing. P. Ciferri

In Ponte di Piave 16/04/2020



DoP in Pdf format are available in the Polyglass SpA website.

Version 2 notes: Changed tensile properties

 0497 1417	 Via Dell'Artigianato, 34 31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
14 CPR-IT4/ B1274 rev. 16/04/2020 EN 13970 POLYVAP SA P-AL Bitumen water vapour control layers	
Reaction to fire	Classe E
Watertightness (Method B)	Meet requirements
Tensile properties Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	400/200 (±20%) N/50 mm 30/30 (±15) %
Resistance to impact (Method A)	≥ 600 mm
Resistance to tearing (longitudinal/transverse)	100/100 (±30%) N
Flexibility at low temperature	≤ -25 °C
Water vapor permeability	≥ 1.000.000 μ
Durability After exposure to artificial ageing Against chemicals	± 50% V.I. ± 50% V.I.
Dangerous substances	NPD

Note:

Polyglass supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*