

EKSPLUATĀCIJAS ĪPAŠĪBU DEKLARĀCIJA No. CPR-NO1/0227

1. Unikāls produkta tipa identifikācijas kods: **UNIPLAN ECO TDR**
2. Tipa, partijas vai sērijas numurs vai kāds cits būvizstrādājuma identifikācijas elements, kā noteikts CPR 11. panta 4. Punktā:

CEMENTA BĀZES PAŠIZLĪDZINOŠS SASTĀVS PAMATNĒM (CT-C40-F10).

3. Būvizstrādājuma paredzētais pielietojums vai pielietojumi, saskaņā ar piemērojamo saskaņoto tehnisko specifikāciju, kā paredzējis ražotājs:

Cementa bāzes klona izveides sastāvs grīdu konstrukcijām iekšdarbos

4. Ražotāja nosaukums, reģistrētais komercnosaukums vai reģistrētā preču zīme un kontaktadrese, kā noteikts 11. panta 5. punktā: **MAPEI AS – Vallsetvegen, 6 – 2120 Sagstua (Norway)**
www.mapei.no
5. Vajadzības gadījumā tā pilnvarotā pārstāvja vārds un kontaktadrese, kura pilnvaras attiecas uz 12. panta 2. punktā nosauktajiem uzdevumiem: **Nav piemērojams**
6. Eksploatācijas īpašību noturības novērtējuma un pārbaudes sistēma vai sistēmas, kā noteikts V pielikumā: **Sistēma 4**
7. Gadījumā, ja eksploatācijas īpašību deklarācija attiecas uz būvizstrādājumu, kuram ir saskaņotais standarts:
Nav nepieciešama izpildinstitūcijas iesaistīšana
8. Gadījumā, ja eksploatācijas īpašību deklarācija attiecas uz būvizstrādājumu, kuram ir izdots Eiropas tehniskais novērtējums: **Nav piemērojams**
9. Deklarētās eksploatācijas īpašības:

Būtiskākie raksturlielumi	Veiktspēja	Saskaņota tehniskā specifikācija
Uguns reakcija Kodīgu sastāvdaļu izdalīšanās: Ūdens caurlaidība: Ūdens tvaiku caurlaidība: Spiedes stiprība: Lieces stiprība: Noturība pret berzi: Skaņas izolēspēja: Skaņas absorbētspēja: Termālā noturība: Ķīmiskā noturība:	F CT NPD NPD C40 F10 NPD NPD NPD NPD NPD	EN 13813:2002

10. Pielikuma 1. un 2. punktā norādītā izstrādājuma eksploatācijas īpašības atbilst 9. punktā norādītajām deklarētajām eksploatācijas īpašībām.

Par šo izdoto eksploatācijas īpašību deklarāciju ir atbildīgs vienīgi 4. punktā norādītais ražotājs.

Parakstīts ražotāja vārdā: **Trond Hagerud**

– **Izpilddirektors**
(vārds, uzvārds, amats)

Sagstua, 01/07/2013

(Izdošanas vieta un datums)

(paraksts)

CE zīme saskaņā ar CPR 305/2011 un EN 13813:2002

	 MAPEI AS – Vallsetvegen, 6 – 2120 Sagstua (Norway) www.mapei.no																						
13 CPR-NO1/0227 EN 13813:2002 CT-C40-F10 UNIPLAN ECO TDR <i>Cementitious screed material for internal use in floor construction</i> <table><tr><td>Reaction to fire:</td><td>F</td></tr><tr><td>Release of corrosive substances:</td><td>SR</td></tr><tr><td>Water permeability:</td><td>NPD</td></tr><tr><td>Water vapour permeability:</td><td>NPD</td></tr><tr><td>Compressive strength:</td><td>C40</td></tr><tr><td>Flexural strength:</td><td>F10</td></tr><tr><td>Wear resistance:</td><td>NPD</td></tr><tr><td>Sound insulation:</td><td>NPD</td></tr><tr><td>Sound absorption:</td><td>NPD</td></tr><tr><td>Thermal resistance:</td><td>NPD</td></tr><tr><td>Chemical resistance:</td><td>NPD</td></tr></table>		Reaction to fire:	F	Release of corrosive substances:	SR	Water permeability:	NPD	Water vapour permeability:	NPD	Compressive strength:	C40	Flexural strength:	F10	Wear resistance:	NPD	Sound insulation:	NPD	Sound absorption:	NPD	Thermal resistance:	NPD	Chemical resistance:	NPD
Reaction to fire:	F																						
Release of corrosive substances:	SR																						
Water permeability:	NPD																						
Water vapour permeability:	NPD																						
Compressive strength:	C40																						
Flexural strength:	F10																						
Wear resistance:	NPD																						
Sound insulation:	NPD																						
Sound absorption:	NPD																						
Thermal resistance:	NPD																						
Chemical resistance:	NPD																						

Declaration of performance: No. CPR-NO1/0227

1. Unique identification code of the product-type: **UNIPLAN ECO TDR**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

CEMENTITIOUS SELF-LEVELLING COMPOUND FOR SUBSTRATES (CT-C40-F10)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Cementitious screed material for internal use in floor construction

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI AS – Vallsetvegen 6, 2120 Sagstua (Norway)**
www.mapei.no
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

No tasks for notified body


8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire Release of corrosive substances: Water permeability: Water vapour permeability: Compressive strength: Flexural strength: Wear resistance: Sound insulation: Sound absorption: Thermal resistance: Chemical resistance:	F CT NPD NPD C40 F10 NPD NPD NPD NPD NPD	EN 13813:2002

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Trond Hagerud – General Manager**
(name and function)



Sagstua, 01/07/2013
(place and date of issue)

(signature)

CE MARKING according to CPR 305/2011 and EN 13813:2002

	 Vallsetvegen 6, 2120 Sagstua (Norway) www.mapei.no
13 CPR-NO1/0227 EN 13813:2002 CT-C40-F10 UNIPLAN ECO TDR <i>Cementitious screed material for internal use in floor construction</i>	
Reaction to fire:	F
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C40
Flexural strength:	F10
Wear resistance:	NPD
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD