

EKSPLUATĀCIJAS ĪPAŠĪBU DEKLARĀCIJA **N. CPR-NO1/0427**

- 1) Unikāls produkta tipa identifikācijas kods: **Maefloor PU 435 SL**
- 2) Paredzētais pielietojums: **Poliuretāna klona izveides materiāls grīdām iekšdarbos**
- 3) Ražotājs: **MAPEI AS – Vallsetvegen, 6 – 2120 Sagstua (Norway) www.mapei.no**
- 4) Sistēma AVCP: **Sistēma 4**
Sistēma 3, ugunsdrošības noteikšanai
- 5) Vienotais standarts: **EN 13813:2002**

Izpildinstitūcijas: **Laboratorija Warringtonfire N. 1378**, veikusi novērtējumu (uguns reakcijas noteikšana), pamatojoties uz testa paraugiem, ko iesniedzis ražotājs.

- 6) Deklarētās veiktspējas īpašības:

Būtiskākie raksturlielumi	Ekspluatācijas īpašības
Ugunsdrošība:	Klase B_{FL}-s1
Kodīgu daļiņu izdalīšanās:	SR
Ūdens caurlaidība:	NPD
Berzes noturība:	AR0,5
Adhēzijas stiprība:	B2,0
Triecienizturība:	IR4
Skaņas izolācija:	NPD
Skaņas absorbētspēja:	NPD
Termālā noturība:	NPD
Ķīmiskā noturība:	NPD

- 7) REACH informācija: informācija, kas minēta REACH Regulas (EK) Nr. 1907/2006 31. punktā vai, attiecīgā gadījumā, 33. punktā un turpmākajos grozījumos, ir norādīti drošības datu lapā, kas pieejama MAPEI mājas lapā, kopā ar šo spēkā esošo Ekspluatācijas īpašību deklarāciju.

Augstāk norādītā produkta veiktspēja atbilst deklarētajām īpašībām.

Šī ekspluatācijas īpašību deklarācija ir izsniegta saskaņā ar Regulu (ES) Nr 305/2011, ar pilnu iepriekš norādītā ražotāja atbildību.

Parakstīts ražotāja vārdā: **Trond Hagerud – Izpilddirektors**

Sagstua, 06/05/2020

EĪD PDF formātā ir pieejamas Mapei mājas lapā

<i>Pārskats 0</i>	<i>Pirmais izdevums</i>
-------------------	-------------------------

 1378	 Valsetvegen 6 - 2120 Sagstua - Norway www.mapei.no																				
20 CPR-NO1/0427 EN 13813 Mapefloor PU 435 SL <i>Polyurethane screed material for internal flooring</i>																					
<table><tr><td>Reaction to fire:</td><td>Class BFL-s1</td></tr><tr><td>Release of corrosive substances:</td><td>SR</td></tr><tr><td>Water permeability:</td><td>NPD</td></tr><tr><td>Wear resistance:</td><td>AR0,5</td></tr><tr><td>Bond strength:</td><td>B2,0</td></tr><tr><td>Impact resistance:</td><td>IR4</td></tr><tr><td>Sound insulation:</td><td>NPD</td></tr><tr><td>Sound absorption:</td><td>NPD</td></tr><tr><td>Thermal resistance:</td><td>NPD</td></tr><tr><td>Chemical resistance:</td><td>NPD</td></tr></table>		Reaction to fire:	Class BFL-s1	Release of corrosive substances:	SR	Water permeability:	NPD	Wear resistance:	AR0,5	Bond strength:	B2,0	Impact resistance:	IR4	Sound insulation:	NPD	Sound absorption:	NPD	Thermal resistance:	NPD	Chemical resistance:	NPD
Reaction to fire:	Class BFL-s1																				
Release of corrosive substances:	SR																				
Water permeability:	NPD																				
Wear resistance:	AR0,5																				
Bond strength:	B2,0																				
Impact resistance:	IR4																				
Sound insulation:	NPD																				
Sound absorption:	NPD																				
Thermal resistance:	NPD																				
Chemical resistance:	NPD																				

Piezīme:

MAPEI nodrošina šo pielikumu kopā ar EĪD, lai atvieglotu CE marķējuma skaidrojumu starptautiskajiem klientiem. Pievienotais CE marķējums var būt nedaudz atšķirīgs, salīdzinot ar to, kas norādīts uz attiecīgā iepakojuma vai dokumentācijas, jo:

- Dēļ grafiskā pielāgojuma uz iepakojuma vai izmantotās drukāšanas metodes,
- Dēļ valodu atšķirības (viens iepakojums vairākām valstīm),
- produkts ir jau krājumā uz brīdi, kad tiek ieviests CE marķējuma atjauninājums,
- Drukas kļūdas dēļ.

DECLARATION OF PERFORMANCE N. CPR-NO1/0427

- 1) Unique identification code of the product-type: **MAPEFLOOR PU 435 SL**
- 2) Intended uses: **Polyurethane screed material for internal flooring**
- 3) Manufacturer: **MAPEI AS – Valsetvegen 6 – 2120 Sagstua – Norway – www.mapei.no**
- 4) Systems of AVCP: **System 4**
System 3 (for reaction to fire)
- 5) Harmonized standards: **EN 13813:2002**

Notified bodies: **The notified laboratory Warringtonfire N. 1378, carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer**

- 6) Performances declared:


Essential characteristics	Performances
Reaction to fire:	Class B_{FL}-s1
Release of corrosive substances:	SR
Water permeability:	NPD
Wear resistance:	AR0,5
Bond strength:	B2,0
Impact resistance:	IR4
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

- 7) REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data sheet that MAPEI makes available on the website along with this current Declaration of Performance.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Trond Hagerud – General Manager**

Sagstua, 06/05/2020



DoP in Pdf format are available in the Mapei website.

Revision 0 notes:	First issue
--------------------------	--------------------

MAPEFLOOR PU 435 SL
CE MARKING
Annex to DoP N. CPR-NO1/0427



 1378	 Valsetvegen 6 - 2120 Sagstua - Norway www.mapei.no																				
20 CPR-NO1/0427 EN 13813 MAPEFLOOR PU 435 SL <i>Polyurethane screed material for internal flooring</i>																					
<table><tr><td>Reaction to fire:</td><td>Class BFL-s1</td></tr><tr><td>Release of corrosive substances:</td><td>SR</td></tr><tr><td>Water permeability:</td><td>NPD</td></tr><tr><td>Wear resistance:</td><td>AR0,5</td></tr><tr><td>Bond strength:</td><td>B2,0</td></tr><tr><td>Impact resistance:</td><td>IR4</td></tr><tr><td>Sound insulation:</td><td>NPD</td></tr><tr><td>Sound absorption:</td><td>NPD</td></tr><tr><td>Thermal resistance:</td><td>NPD</td></tr><tr><td>Chemical resistance:</td><td>NPD</td></tr></table>		Reaction to fire:	Class BFL-s1	Release of corrosive substances:	SR	Water permeability:	NPD	Wear resistance:	AR0,5	Bond strength:	B2,0	Impact resistance:	IR4	Sound insulation:	NPD	Sound absorption:	NPD	Thermal resistance:	NPD	Chemical resistance:	NPD
Reaction to fire:	Class BFL-s1																				
Release of corrosive substances:	SR																				
Water permeability:	NPD																				
Wear resistance:	AR0,5																				
Bond strength:	B2,0																				
Impact resistance:	IR4																				
Sound insulation:	NPD																				
Sound absorption:	NPD																				
Thermal resistance:	NPD																				
Chemical resistance:	NPD																				

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.