

EKSPLUATĀCIJAS ĪPAŠĪBU DEKLARĀCIJA No. CPR-IT1/0093

- Unikāls produkta tipa identifikācijas kods: **Mapefloor I 914**
- Tipa, partijas vai sērijas numurs vai kāds cits būvizstrādājuma identifikācijas elements, kā noteikts CPR 11. panta 4. Punktā:
**DIVKOMPONENTU BETONA INJEKCIJU PRODUKTS, KURA SASTĀVĀ IR REAKTĪVA POLIMĒRU SAISTVIELA
U(F1)W(2)(1/2)(5/35)**
- Būvizstrādājuma paredzētais pielietojums vai pielietojumi, saskaņā ar piemērojamo saskaņoto tehnisko specifikāciju, kā paredzējis ražotājs:
Produkts betona konstrukciju remontam un aizsardzībai, pārnesot spriedzes ar plaisu aizpildi
- Ražotāja nosaukums, reģistrētais komercnosaukums vai reģistrētā preču zīme un kontaktadrese, kā noteikts 11. panta 5. punktā: **MAPEI S.p.A. Via Cafiero, 22 – 20158 Milano (Italy)
www.mapei.it**
- Vajadzības gadījumā tā pilnvarotā pārstāvja vārds un kontaktadrese, kura pilnvaras attiecas uz 12. panta 2. punktā nosauktajiem uzdevumiem: **Nav piemērojams**
- Ekspluatācijas īpašību noturības novērtējuma un pārbaudes sistēma vai sistēmas, kā noteikts V pielikumā: **Sistēma 2+**
- Gadījumā, ja ekspluatācijas īpašību deklarācija attiecas uz būvizstrādājumu, kuram ir saskaņotais standarts:
Izpildinstitūcija ICMQ S.p.A., nr. 1305 veikusi sākotnējo ražotnes un ražošanas kvalitātes kontroles un uzraudzības pārbaudi, novērošanu un novērtēšanu sistēma 2+ ietvaros un ir izsniegusi rūpnīcas ražošanas kontroles atbilstības sertifikātu nr. 1305-CPD-0616.
- Gadījumā, ja ekspluatācijas īpašību deklarācija attiecas uz būvizstrādājumu, kuram ir izdots Eiropas tehniskais novērtējums: **Nav piemērojams**
- Deklarētās ekspluatācijas īpašības:

Būtiskākie raksturlielumi	Veiktspēja	Saskaņota tehniskā specifikācija
Stiepes stiprības adhēzija: Slīpas bīdes stiprības adhēzija: Rukums: Pārstiklošanās temperatūra: Izstrādājamība: - plaisu platums: - plaisas mitruma stāvoklis: Ilgmūžība: Korozivitāte: Bīstamas sastāvdaļas:	Pamatnes kohēzijas zudums: Monolītas pamatnes zudums: < 3 % > 40°C no 0,2 mm Sauss vai nedaudz mitrs Atbilst tiek uzskatīts, ka produktam nepiemīt kodīgums NPD	EN 1504-5:2004

- Pielikuma 1. un 2. punktā norādītā izstrādājuma ekspluatācijas īpašības atbilst 9. punktā norādītajām deklarētajām ekspluatācijas īpašībām.

Par šo izdoto ekspluatācijas īpašību deklarāciju ir atbildīgs vienīgi 4. punktā norādītais ražotājs.

Parakstīts ražotāja vārdā: **Paolo Murelli – Korporatīvā Kvalitātes Vadība**
(vārds, uzvārds, amats)

Milan, 01/07/2013

(Izdošanas vieta un datums)

.....
(paraksts)

CE MARKING according to CPR 305/2011 and EN 1504-5:2004

 1305	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it																				
13 CPR-IT1/0093 EN 1504-5:2004 Mapectfloor I 914 <i>Concrete injection product formulated with reactive polymer binder for force transmitting filling of cracks: U(F1)W(2)(1/2)(5/35)</i> <table><tr><td>Adhesion by tensile bond strength:</td><td>cohesive failure in the substrate</td></tr><tr><td>Adhesion by slant shear strength:</td><td>monolithic failure</td></tr><tr><td>Shrinkage:</td><td>< 3%</td></tr><tr><td>Glass transition temperature:</td><td>> 40°C</td></tr><tr><td>Workability:</td><td></td></tr><tr><td>- crack width:</td><td>from 0,2 mm</td></tr><tr><td>- moisture state of the crack</td><td>dry and damp</td></tr><tr><td>Durability:</td><td>Passes</td></tr><tr><td>Corrosion behaviour:</td><td>deemed to have no corrosive effect</td></tr><tr><td>Dangerous substances:</td><td>NPD</td></tr></table>		Adhesion by tensile bond strength:	cohesive failure in the substrate	Adhesion by slant shear strength:	monolithic failure	Shrinkage:	< 3%	Glass transition temperature:	> 40°C	Workability:		- crack width:	from 0,2 mm	- moisture state of the crack	dry and damp	Durability:	Passes	Corrosion behaviour:	deemed to have no corrosive effect	Dangerous substances:	NPD
Adhesion by tensile bond strength:	cohesive failure in the substrate																				
Adhesion by slant shear strength:	monolithic failure																				
Shrinkage:	< 3%																				
Glass transition temperature:	> 40°C																				
Workability:																					
- crack width:	from 0,2 mm																				
- moisture state of the crack	dry and damp																				
Durability:	Passes																				
Corrosion behaviour:	deemed to have no corrosive effect																				
Dangerous substances:	NPD																				

Declaration of performance: No. CPR-IT1/0093

1. Unique identification code of the product-type: **MAPEFLOOR I 914**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
**TWO-COMPONENT CONCRETE INJECTION PRODUCT FORMULATED WITH REACTIVE POLYMER BINDER
U(F1)W(2)(1/2)(5/35)**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Product for the repair and protection of concrete structure by force transmitting filling of cracks
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI S.p.A. – Via Cafiero, 22 – Milano (Italy)**
www.mapei.it
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 2+**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
The Notified Body ICMQ S.p.A., No. 1305, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, under system 2+, and issued the certificate of conformity of the factory production control No. 1305-CPD-0616.
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Adhesion by tensile bond strength: Adhesion by slant shear strength: Shrinkage: Glass transition temperature: Workability: - crack width: - moisture state of the crack: Durability: Corrosion behaviour: Dangerous substances:	cohesive failure in the substrate monolithic failure < 3 % > 40°C from 0,2 mm dry and damp Passes deemed to have no corrosive effect NPD	EN 1504-5:2004

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.


This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**

(name and function)

Milan, 01/07/2013

(place and date of issue)



(signature)

CE MARKING according to CPR 305/2011 and EN 1504-5:2004

 1305	 MAPEI Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it																				
13 CPR-IT1/0093 EN 1504-5:2004 MAPEFLOOR I 914 <i>Concrete injection product formulated with reactive polymer binder for force transmitting filling of cracks: U(F1)W(2)(1/2)(5/35)</i> <table><tr><td>Adhesion by tensile bond strength:</td><td>cohesive failure in the substrate</td></tr><tr><td>Adhesion by slant shear strength:</td><td>monolithic failure</td></tr><tr><td>Shrinkage:</td><td>< 3%</td></tr><tr><td>Glass transition temperature:</td><td>> 40°C</td></tr><tr><td>Workability:</td><td></td></tr><tr><td>- crack width:</td><td>from 0,2 mm</td></tr><tr><td>- moisture state of the crack</td><td>dry and damp</td></tr><tr><td>Durability:</td><td>Passes</td></tr><tr><td>Corrosion behaviour:</td><td>deemed to have no corrosive effect</td></tr><tr><td>Dangerous substances:</td><td>NPD</td></tr></table>		Adhesion by tensile bond strength:	cohesive failure in the substrate	Adhesion by slant shear strength:	monolithic failure	Shrinkage:	< 3%	Glass transition temperature:	> 40°C	Workability:		- crack width:	from 0,2 mm	- moisture state of the crack	dry and damp	Durability:	Passes	Corrosion behaviour:	deemed to have no corrosive effect	Dangerous substances:	NPD
Adhesion by tensile bond strength:	cohesive failure in the substrate																				
Adhesion by slant shear strength:	monolithic failure																				
Shrinkage:	< 3%																				
Glass transition temperature:	> 40°C																				
Workability:																					
- crack width:	from 0,2 mm																				
- moisture state of the crack	dry and damp																				
Durability:	Passes																				
Corrosion behaviour:	deemed to have no corrosive effect																				
Dangerous substances:	NPD																				