

EKSPLUATĀCIJAS ĪPAŠĪBU DEKLARĀCIJA No: CPR-NO1/0008

- Unikāls izstrādājuma tipa identifikācijas numurs: **MAPEPRIMER M**
- Tipa, partijas vai sērijas numurs vai kāds cits būvizstrādājuma identifikācijas elements, kā noteikts 11. panta 4. punktā: **Produkts virsmu aizsardzībai - Pārklājums**
- Būvizstrādājuma paredzētais izmantojums vai izmantojumi saskaņā ar piemērojamo saskaņoto tehnisko specifikāciju, kā paredzējis ražotājs:

Produkts, kas paredzēts virsmu aizsardzībai – pārklājums

Aizsardzība pret iesūkšanos pamatnē, Fizikālā noturība, Ķīmiskā noturība

- Ražotāja nosaukums, reģistrētais komercnosaukums vai reģistrētā preču zīme un kontaktadrese, kā noteikts 11. panta 5. punktā: **MAPEI AS – Vallsetvegen, 6 – 2120 Sagstua (Norway) www.mapei.no**
- Vajadzības gadījumā tā pilnvarotā pārstāvja vārds un kontaktadrese, kura pilnvaras attiecas uz 12. panta 2. punktā nosauktajiem uzdevumiem: **Nav piemērojams**
- Ekspluatācijas īpašību noturības novērtējuma un pārbaudes sistēma vai sistēmas, kā noteikts V pielikumā:
Sistēma 2+
Sistēma 4, uguns noturības noteikšanai
- Gadījumā, ja ekspluatācijas īpašību deklarācija attiecas uz būvizstrādājumu, kuram ir saskaņotais standarts: **Izpildinstitūcija nr. 1071 Sintef Building and Infrastructure veikusi sākotnējo ražotnes un ražošanas kvalitātes kontroles un uzraudzības pārbaudi, novērošanu un novērtēšanu, saskaņā ar sistēmu 2+ un ir izsniegusi rūpnīcas ražošanas kontroles atbilstības sertifikātu No. 1071– CPD – 1674.**
- Gadījumā, ja ekspluatācijas īpašību deklarācija attiecas uz būvizstrādājumu, kuram ir izdots Eiropas tehniskais novērtējums: **Nav piemērojams**
- Deklarētās ekspluatācijas īpašības

Būtiskie raksturlielumi	Ekspluatācijas īpašības	Saskaņota tehniskā specifikācija
Spiedes noturība Berzes noturība CO² caurlaidība Ūdens tvaiku caurlaidība Kapilārā absorbētspēja un ūdens caurlaidība Noturība pret agresīvu ķīmisko vielu iedarbību Trieciennoturība Adhēzijas stiprība pie atraušanas Uguns noturība Bīstamas sastāvdaļas	Klase II < 3000 mg NPD NPD NPD NPD Klase I ≥2,0 N/mm² F NPD	EN 1504-2:2004

- Pielikuma 1. un 2. punktā norādītā izstrādājuma ekspluatācijas īpašības atbilst 9. punktā norādītajām deklarētajām ekspluatācijas īpašībām.

Par šo izdoto ekspluatācijas īpašību deklarāciju ir atbildīgs vienīgi 4. punktā norādītais ražotājs.

Parakstīts ražotāja vārdā:

Trond Hagerud – Managing director

(vārds, uzvārds, amats)

Sagstua, 01/07/2013

(izdošanas vieta un datums)

(paraksts)

CE MARKING according to CPR 305/2011 and EN 1504-2:2004

 1071	 Vallsetvegen 6, 2120 Sagstua (Norway) www.mapei.no
13 CPR-NO1/0008 EN 1504-2:2004 MAPEPRIMER M <i>Produkts, kas paredzēts virsmu aizsardzībai – pārklājums</i> <i>Aizsardzība pret iesūkšanos pamatnē, Fizikālā noturība, Ķīmiskā noturība</i>	
Spiedes noturība	Klase II
Berzes noturība	< 3000 mg
CO2 caurlaidība	NPD
Ūdens tvaiku caurlaidība	NPD
Kapilārā absorbētspēja un ūdens caurlaidība	NPD
Noturība pret agresīvu ķīmisko vielu iedarbību	NPD
Trieciennoturība	Klase I
Adhēzijas stiprība pie atraušanas	≥2,0 N/mm2
Uguns noturība	F
Bīstamas sastāvdaļas	NPD

Declaration of performance: No. CPR-NO1/0008

1. Unique identification code of the product-type: **MAPEPRIMER M**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

SURFACE PROTECTION PRODUCT – COATING

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Intended to be used as surface protection products – coating

1.3 Ingress protection, 5.1 Physical resistance, 6.1 Chemical resistance

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI AS – Vallsetvegen 6 – 2120 Sagstua (Norway) www.mapei.no**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 2+
System 4 for reaction to fire
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
The Notified Body Sintef Building and Infrastructure No. 1071, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, under system 2+, and issued the certificates of conformity of the factory production control No. 1071– CPD – 1674.
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Compressive strength	Class II	EN 1504-2:2004
Abrasion resistance	< 3000 mg	
Permeability to CO₂	NPD	
Water vapour permeability	NPD	
Capillary absorption and permeability to water	NPD	
Resistance to severe chemical attack	NPD	
Impact resistance	Class I	
Adhesion strength by pull off test	≥2,0 N/mm²	
Reaction to fire	F	
Dangerous substances	NPD	


10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Trond Hagerud – Managing Director**

Sagstua, 01/07/2013

(place and date of issue)


.....
(signature)

CE MARKING according to CPR 305/2011 and EN 13813:2002

 1071	 MAPEI Vallsetvegen 6, 2120 Sagstua (Norway) www.mapei.no																				
13 CRP-NO1/0008 EN 1504-2:2004 MAPEPRIMER M Intended to be used as surface protection products – coating 1.3 Ingress protection 5.1 Physical resistance 6.1 Chemical resistance <table><tr><td>Compressive strength</td><td>Class II</td></tr><tr><td>Abrasion resistance</td><td>< 3000 mg</td></tr><tr><td>Permeability to CO₂</td><td>NPD</td></tr><tr><td>Water vapour permeability</td><td>NPD</td></tr><tr><td>Capillary absorption and permeability to water</td><td>NPD</td></tr><tr><td>Resistance to severe chemical attack</td><td>NPD</td></tr><tr><td>Impact resistance</td><td>Class I</td></tr><tr><td>Adhesion strength by pull off test</td><td>≥2,0 N/mm²</td></tr><tr><td>Reaction to fire</td><td>F</td></tr><tr><td>Dangerous substances</td><td>NPD</td></tr></table>		Compressive strength	Class II	Abrasion resistance	< 3000 mg	Permeability to CO ₂	NPD	Water vapour permeability	NPD	Capillary absorption and permeability to water	NPD	Resistance to severe chemical attack	NPD	Impact resistance	Class I	Adhesion strength by pull off test	≥2,0 N/mm ²	Reaction to fire	F	Dangerous substances	NPD
Compressive strength	Class II																				
Abrasion resistance	< 3000 mg																				
Permeability to CO ₂	NPD																				
Water vapour permeability	NPD																				
Capillary absorption and permeability to water	NPD																				
Resistance to severe chemical attack	NPD																				
Impact resistance	Class I																				
Adhesion strength by pull off test	≥2,0 N/mm ²																				
Reaction to fire	F																				
Dangerous substances	NPD																				