



# Ultracoat Oil Color

**Low-odour urethane oil finish for colouring wooden floors. It can be painted over with the Ultracoat finishes**



## WHERE TO USE

Colouring treatment for wooden floors. Available in white, black, walnut, mahogany, cherry red, grey, grey wave.

## TECHNICAL CHARACTERISTICS

**Ultracoat Oil Color** is used for impregnating and colouring wood. Due to its special formulation **Ultracoat Oil Color** may be used to colour wooden floors and, thanks to its compatibility with **Ultracoat** finishing products, it gives the surface a highly-protective, long-lasting coloured finish.

## RECOMMENDATIONS

- Do not use **Ultracoat Oil Color** at temperatures lower than +10°C.
- Use only clean containers and tools.
- Do not put leftovers of the product back into its original container.

All tools used to apply the product, such as rollers, brushes, pads and cotton rags, must be soaked in water immediately after use to prevent the risk of self-combustion.

## APPLICATION PROCEDURE

### Substrate preparation

Sand the surface of the floor to get the desired finish and remove all traces of dirt and dust before applying the protective finish.

## Application

**Ultracoat Oil Color** is supplied ready to use; mix for a few minutes prior to application.

### Medium-high protection finish

Apply a generous coat of **Ultracoat Oil Color** with **Ultracoat Roller T3**. After 30 to 45 minutes the wood is completely saturated; remove any excess of **Ultracoat Oil Color** with a single-head sander fitted with **Ultracoat Pad White** and a cotton rag or **Ultracoat Oil Pad**.

When applying the product on large surfaces, we recommend dividing it into smaller areas around 20 to 25 m<sup>2</sup> each.

Leave it to dry for at least 16 hours and then buff the surface with a single-head sander with a **Ultracoat Pad Green**. Carefully remove all the dust and apply a coat of **Ultracoat High Traffic** or **Ultracoat Soft Touch Finish**. Leave it to dry for at least 24 hours and then buff the surface with a **Ultracoat SR 220** or **Ultracoat Pad Special Stripper** pad. Carefully remove all the dust again and apply a further coat of **Ultracoat High Traffic** or **Ultracoat Soft Touch Finish**.

### Low protection finish

Apply a generous coat of **Ultracoat Oil Color** with an **Ultracoat Roller T3**. After 30 to 45 minutes the wood is completely saturated; remove any excess colour oil with a single-head sander with a **Ultracoat White Pad** and a cotton rag or **Ultracoat Oil Pad**.

When applying the product on large surfaces, we recommend dividing it into smaller areas around 20 to 25 m<sup>2</sup> each.

# Ultracoat Oil Color



Application of the product with a roller



After sanding application of Ultracoat two-component, water-based varnish

## TECHNICAL DATA (typical values)

### PRODUCT IDENTITY

Consistency:	fluid
Appearance:	coloured oil
Colours available:	white, black, walnut, mahogany, cherry red, grey, grey wave
Density (g/cm <sup>3</sup> ):	0.8
Application temperature range:	+10°C - +25°C
Application:	roller, brush, pad or trowel
Removal time:	35 to 45 minutes
Buffing:	16 hours with a <b>Ultracoat Pad Green</b>
Ready for service:	3 days

Leave it to dry for at least 16 hours and then buff the surface with a single-head sander with a **Ultracoat Pad Black**. Carefully remove all the dust and apply two coats of **Ultracoat Oil Care**.

For a more intense colour, apply more **Ultracoat Oil Color** after buffing the surface with the **Ultracoat Pad Green**.

### Cleaning

Clean tools and remove residues of **Ultracoat Oil Color** with **Pulicol 2000** while the product is still fresh.

### CONSUMPTION

1 litre every 10 to 50 m<sup>2</sup> depending on the absorption of the wood and the intensity of colour required.

### STORAGE

24 months in its original packaging in a dry place.

### PACKAGING

2.5 litres.

### SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

**Ultracoat Oil Color** is dangerous for aquatic life. Do not dispose of it in the environment. During use, it is recommended to wear gloves to prevent dry, chapped skin, safety goggles and to take the usual precautions for handling chemicals. If the product comes in contact with the eyes or skin, wash immediately with plenty of clean water and seek medical attention.

For further and complete information about the safe use of our product please refer to the latest version of our Material Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

### WARNING

*Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.*

Please refer to the current version of the **Technical Data Sheet**, available from our website [www.mapei.com](http://www.mapei.com)

### LEGAL NOTICE

*The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.*

*The most up-to-date TDS can be downloaded from our website [www.mapei.com](http://www.mapei.com).*

**ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.**

**All relevant references for the product are available upon request and from [www.mapei.com](http://www.mapei.com)**



BUILDING THE FUTURE