

EKSPLOATĀCIJAS ĪPAŠĪBU DEKLARĀCIJA No. CPR-NO1/0332

1. Unikāls produkta tipa identifikācijas kods: **CONPLAN ECO**
2. Tipa, partijas vai sērijas numurs vai kāds cits būvizrādājuma identifikācijas elements, kā noteikts CPR 11. panta 4. Punktā:

CEMENTA BĀZES PAŠIZLĪDZINOŠS SASTĀVS PAMATNĒM (CT-C30-F7).

3. Būvizrādājuma paredzētais izmantojums vai izmantojumi saskaņā ar piemērojamo saskaņoto tehnisko specifikāciju, kā paredzējis ražotājs:

Cementa bāzes grīdu izveides materiāls iekštelpām

4. Ražotāja nosaukums, reģistrētais komercnosaukums vai reģistrētā preču zīme un kontaktadrese, kā noteikts 11. panta 5. punktā: **MAPEI AS – Vallsetvegen, 6 – 2120 Sagstua (Norway) www.mapei.no**
5. Vajadzības gadījumā tā pilnvarotā pārstāvja vārds un kontaktadrese, kura pilnvaras attiecas uz 12. panta 2. punktā nosauktajiem uzdevumiem: **Nav piemērojams**
6. Eksploatācijas īpašību noturības novērtējuma un pārbaudes sistēma vai sistēmas, kā noteikts V pielikumā:
Sistēma 4
Sistēma 3, uguns reakcijas noteikšanai
7. Gadījumā, ja eksploatācijas īpašību deklarācija attiecas uz būvizrādājumu, kuram ir saskaņotais standarts:
Pilnvarotā testēšanas laboratorijā MPA Dresden GmbH N. 0767 veikta ugunsdrošības klases noteikšana izmantojot ražotāja iesniegtos paraugus, 3. sistēmas ietvaros un izsniegts ziņojums nr. 2013-B-1970/01.
8. Gadījumā, ja eksploatācijas īpašību deklarācija attiecas uz būvizrādājumu, kuram ir izdots Eiropas tehniskais novērtējums: **Nav piemērojams**
9. Deklarētās eksploatācijas īpašības:

Būtiskākie raksturlielumi	Veiktspēja	Saskaņota tehniskā specifikācija
Uguns reakcija: Kodīgu sastāvdaļu izdalīšanās: Ūdens caurlaidība: Ūdens tvaiku caurlaidība: Spiedes stiprība: Lieces stiprība: Berzes noturība: Skaņas izolētspēja: Skaņas absorbētspēja: Termālā noturība: Ķīmiskā noturība:	Klase A2 _{fl-s1} CT NPD NPD C30 F7 NPD NPD NPD NPD NPD	EN 13813:2002

10. Pielikuma 1. un 2. punktā norādītā izstrādājuma eksploatācijas īpašības atbilst 9. punktā norādītajām deklarētajām eksploatācijas īpašībām. Par šo izdoto eksploatācijas īpašību deklarāciju ir atbildīgs vienīgi 4. punktā norādītais ražotājs.

Parakstīts ražotāja vārdā: (vārds, uzvārds, amats)

Trond Hagerud – Izpilddirektors

Izdošanas vieta un datums:

Sagstua, 10/02/2015

CE zīme saskaņā ar CPR 305/2011 un EN 13813:2002

 0767	 MAPEI AS – Vallsetvegen, 6 – 2120 Sagstua (Norway) www.mapei.no																						
13 CPR-NO1/0332 EN 13813:2002 CT-C30-F7 CONPLAN ECO <i>Cementitious screed material for internal use in floor construction</i> <table><tr><td>Reaction to fire:</td><td>Class A2_{fl}-s1</td></tr><tr><td>Release of corrosive substances:</td><td>CT</td></tr><tr><td>Water permeability:</td><td>NPD</td></tr><tr><td>Water vapour permeability:</td><td>NPD</td></tr><tr><td>Compressive strength:</td><td>C30</td></tr><tr><td>Flexural strength:</td><td>F7</td></tr><tr><td>Wear resistance:</td><td>NPD</td></tr><tr><td>Sound insulation:</td><td>NPD</td></tr><tr><td>Sound absorption:</td><td>NPD</td></tr><tr><td>Thermal resistance:</td><td>NPD</td></tr><tr><td>Chemical resistance:</td><td>NPD</td></tr></table>		Reaction to fire:	Class A2 _{fl} -s1	Release of corrosive substances:	CT	Water permeability:	NPD	Water vapour permeability:	NPD	Compressive strength:	C30	Flexural strength:	F7	Wear resistance:	NPD	Sound insulation:	NPD	Sound absorption:	NPD	Thermal resistance:	NPD	Chemical resistance:	NPD
Reaction to fire:	Class A2 _{fl} -s1																						
Release of corrosive substances:	CT																						
Water permeability:	NPD																						
Water vapour permeability:	NPD																						
Compressive strength:	C30																						
Flexural strength:	F7																						
Wear resistance:	NPD																						
Sound insulation:	NPD																						
Sound absorption:	NPD																						
Thermal resistance:	NPD																						
Chemical resistance:	NPD																						

Declaration of performance: No. CPR-NO1/0332

1. Unique identification code of the product-type: **CONPLAN ECO**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

CEMENTITIOUS SELF-LEVELLING COMPOUND FOR SUBSTRATES (CT-C30-F7)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Cementitious screed material for internal use in floor construction

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI AS – Vallsetvegen 6, 2120 Sagstua (Norway) www.mapei.no**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4
System 3 for reaction to fire
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
The notified testing laboratory MPA Dresden GmbH N. 0767, performed the determination of the class of reaction to fire on samples taken by the manufacturer, under system 3, and issues the report N. 2013-B-1970/01
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance


Essential characteristics	Performance	Harmonised technical specification
Reaction to fire Release of corrosive substances: Water permeability: Water vapour permeability: Compressive strength: Flexural strength: Wear resistance: Sound insulation: Sound absorption: Thermal resistance: Chemical resistance:	Class A2_{fl}-s1 CT NPD NPD C30 F7 NPD NPD NPD NPD NPD	EN 13813:2002

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Trond Hagerud – General Manager**
(name and function)

Sagstua, 10/02/2015
(place and date of issue)


(signature)

CE MARKING according to CPR 305/2011 and EN 13813:2002

 0767	 Vallsetvegen 6, 2120 Sagstua (Norway) www.mapei.no																						
13 CPR-NO1/0332 EN 13813:2002 CT-C30-F7 CONPLAN ECO <i>Cementitious screed material for internal use in floor construction</i> <table><tr><td>Reaction to fire:</td><td>Class A2_{fl}-s1</td></tr><tr><td>Release of corrosive substances:</td><td>CT</td></tr><tr><td>Water permeability:</td><td>NPD</td></tr><tr><td>Water vapour permeability:</td><td>NPD</td></tr><tr><td>Compressive strength:</td><td>C30</td></tr><tr><td>Flexural strength:</td><td>F7</td></tr><tr><td>Wear resistance:</td><td>NPD</td></tr><tr><td>Sound insulation:</td><td>NPD</td></tr><tr><td>Sound absorption:</td><td>NPD</td></tr><tr><td>Thermal resistance:</td><td>NPD</td></tr><tr><td>Chemical resistance:</td><td>NPD</td></tr></table>		Reaction to fire:	Class A2 _{fl} -s1	Release of corrosive substances:	CT	Water permeability:	NPD	Water vapour permeability:	NPD	Compressive strength:	C30	Flexural strength:	F7	Wear resistance:	NPD	Sound insulation:	NPD	Sound absorption:	NPD	Thermal resistance:	NPD	Chemical resistance:	NPD
Reaction to fire:	Class A2 _{fl} -s1																						
Release of corrosive substances:	CT																						
Water permeability:	NPD																						
Water vapour permeability:	NPD																						
Compressive strength:	C30																						
Flexural strength:	F7																						
Wear resistance:	NPD																						
Sound insulation:	NPD																						
Sound absorption:	NPD																						
Thermal resistance:	NPD																						
Chemical resistance:	NPD																						